Westinghouse

# Specification Sheet

# General Purpose™ A19 Dimmable LED Lamp

**Item Number** 03436

## Specifications

| | |
|---|---|
| Energy Used (Watts) | 8 |
| Incandescent Equivalent Wattage | 40 |
| Domestic Code | 8A19/LED/DIM/30/RP |
| Volts | 120 |
| Brightness (Lumens) | 450 |
| Average Rated Hours | 30,000 |
| Life (in years)* | 27.4 |
| Light Appearance (Kelvin) | 3000 |
| CRI | 80 |
| CIE Chromaticity | x.440, y.403 |
| Efficacy (LPW) | 56 |
| PF | ≥.7 |
| Minimum Starting Temperature | -20°C/-4°F |
| Estimated Yearly Energy Cost** | $0.96 |
| Country of Origin | Taiwan |

## Physical Characteristics

| | |
|---|---|
| Finish | Warm White |
| Housing Material | Aluminum |
| Base | Medium |
| MOL | 4⅜" |

c UL us LISTED

RoHS COMPLIANT 2002/95/EC

DAMP

## Limited Warranty

This lamp is warranted to be free from defects in material and workmanship for 3 years (based on using 3 hours per day). If the product fails during the warranty period, return defective product to retailer. Warranty terms and conditions of retailer apply. If replacement product is not available at retail store, please return product, original package and receipt to manufacturer at: 12401 McNulty Road, Philadelphia, PA 19154-1029.

## Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock - Do not use where exposed to water or weather.
- Suitable for Damp Locations - The lamp is suitable for use in damp locations when used in an outdoor rated luminaire.
- Not for use in totally enclosed luminaires.
- Do not open – no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

* Based on 3 hrs./day

* * Based on 3 hrs./day 11¢/kWh - Cost depends on rates and use.

See reverse side for dimmer compatibility

## A19 LED Dimmer Compatibility

| Brand | Model |
|---|---|
| Daiko | DP-34401 |
| Diing Chung | DC-306 |
| Leviton | TBI03 |
| Lutron | Lumea LGCL-153PL, Lumea LG-600P, Toggler TG-600PNL, 6681, Diva DVCL-153PL, Skylark SELVB-300P, Skylark S-603P, Skylark S2-L, Maestro MA-600 Digital, |
| Panasonic | WN576149, WN575149, WN57512 |

©2012 WESTINGHOUSE LIGHTING CORPORATION / WLC / 0412 / 103992

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.



Westinghouse Lighting Corporation, Philadelphia, PA 19154-1029, U.S.A. Westinghouse Lighting Corporation, a Westinghouse Electric Corporation licensee
"Westinghouse" and "You can be sure...if it's Westinghouse"are all registered trademarks of Westinghouse Electric Corporation